

# Sustainable

# PROFESSIONAL MANUFACTURER











www.ortek.com

OEM/ODM WELCOME



# MDS-600

# OS Compatibility

Apple MacBook Pro 2019/2018/2017/2016 MacBook Air 13" 2019/2018 Mac OS 10.12 or later

# **Output Port**

# HDMI

1080p(1920x1080) 4K(3840x2160)

# Ethernet LAN RJ45

1Gb/S

# USB Type A

x 2 GEN 1 (5Gb/s)

# SD Card Slot

microSD full-size SD card support SD UHS-I up to104MB/s

# Dimension

44 x 120 x 12 mm

# Weight

105 g





# **MDS-500**

# OS Compatibility

Apple MacBook Pro 13"or 15" Mac OS 10.12 or later

# **Output Port**

# HDMI

1080p (1920x1080) 4K (3840x2160)

# USB-C

x1 Gen 1 (5Gb/s)

# USB Type A

x2 Gen 1 (5Gb/s)

# Card reader

SD UHS-I up to 104 MB/s

# Dimension

45 x 110 x 10 mm

# Weight

95 g





# **Mini Docking Station**

USB-C bypass port. Supports full-featured USB-C

• Gigabit Ethernet Port supports 10/100/1000 BASE-T Mbps network connection, ideal for streaming movies, downloading large files or playing games

• Downstream port compliant with the USB 3.1 Gen1 super speed 5Gb/s specifications

- Downstream port support SS, HS, FS and low speed(LS) traffic
- Backward compatible with USB specification Revision 2.0/1.1 and 1.0
- Enables portable device to charge from VBUS even when the USB bus is in suspend
- Support individual over-current detection and reverse current flow blocking for all downstream port

### MDS-600

# OS Compatibility

Apple MacBook Pro 2019/2018/2017/2016 MacBook Air 13" 2019/2018 Mac OS 10.12 or later

# Output Port HDMI

1080p(1920x1080) 4K(3840x2160)

Ethernet LAN RJ45

1Gb/S

USB Type A

x 2 GFN 1 (5Gb/s)

# SD Card Slot

microSD full-size SD card support SD UHS-I up to104MB/s

## Dimension

44 x 120 x 12 mm





# **Mini Docking Station**

USB-C bypass port. Supports full-featured USB-C

- USB-C bypass port. Supports full-featured USB-C
- Downstream port compliant with USB 3.1 Gen 1 super speed 5Gb/s specifications
- Downstream port support SS, HS, FS and low speed(LS) traffic
- Backward compatible with USB specification Revision 2.0/1.1/1.0
- Enables portable device to charge from VBUS even when the USB bus is in suspend
- Support individual over-current detection and reverse current flow blocking for all downstream port

# MDS-500

# OS Compatibility

Apple MacBook Pro 13" or 15" Mac OS 1012 or later

# Output Port

1080p (1920x1080) 4K (3840x2160)

# USB-C

x1 Gen 1 (5Gb/s)

# USB Type A

x2 Gen 1 (5Gb/s)

# Card reader

SD UHS-I

up to 104 MB/s

# Dimension

45 x 110 x 10 mm

# Weight

95 g



HDMI Video Ouput 1080p (1920\*1080) @60Hz, up to 4K (3840\*2160) @30Hz









Taipei Head office

Xiamen Factory



Since 1989

USA/EUROPE:

usa-oem@ortek.com

ASIA :

asia-a@ortek.com

JAPAN

jpdep-2@ortek.com





